## AUBURN FIRE DEPARTMENT WOODSTOVE INSTALLATION CHECKLIST

Use this checklist before starting the first fire in your stove to be sure it is safely installed:
The stove does not have broken parts or large cracks that make it unsafe to operate.
The stove is located on a non-combustible floor or an approved floor protection material is placed under the stove.
Floor protection extends out 18 inches from all side of the stove.
The stove is spaced at least 36 inches away from combustible material, or as specified for
a listed stove. If not, properly installed wall protectors are used.
Stove pipe of 24-gauge metal is used.
The stove pipe diameter is not reduced between the stove and the chimney flue.
A damper is installed in the stove pipe near the stove unless one is built into the stove.
The total length of stove pipe is less than 10 feet.
There is at least 18 inches between the stove pipe and the ceiling or other combustible
material.
The stove pipe slopes upward toward the chimney and enters the chimney higher than the
outlet of the stove fire box.
The stove pipe enters the chimney horizontally through fireclay thimble with proper
clearances.
The stove pipe does not extend into the chimney flue lining.
The inside thimble diameter is the same size as the stove pipe for a snug fit or is sealed
with furnace cement.
A double walled ventilated metal thimble is used where the stove pipe goes through an
interior wall.
The store give does not goes through a floor alcost conceled groop or enter the chireness

\_\_\_\_\_ The stove pipe does not pass through a floor, closet, concealed space or enter the chimney in the attic.

\_\_\_\_\_ A UL approved ALL FUEL metal chimney is used where a masonry chimney is not available or practical.

- \_\_\_\_\_ The chimney is in good repair.
- \_\_\_\_\_ The chimney flue lining is not blocked.
- \_\_\_\_\_ The chimney flue lining and the stove pipe are clean.
- \_\_\_\_\_ A metal container with tight fitting lid is available for ash disposal.
- \_\_\_\_\_ The company insuring the building has been notified of the installation.
- \_\_\_\_\_ A smoke detector is installed outside each bedroom area and at the top of the basement stairs.
  - A fire extinguisher (with at least 2A:10B:C-rating) is near the entrance to the room with the stove.