Sec. 60-550 DOWNTOWN TRADITIONAL CENTER T-5.1



Illustrative View of T- 5.1 (Future Great Falls Plaza)

Intent and Purpose: Downtown Traditional Center (T- 5.1)

The Downtown Traditional Center zone is characterized by medium to larger sized buildings in a compact urban environment that generates an active street life. There is interplay between the Public Realm of the busy street and sidewalk, and the Private Realm of the residential stoops, commercial storefronts and gallery building fronts. The increased building widths form a more solid and compact street wall pattern, generating an energized traditional downtown feel.

T-5.1 DOWNTOWN TRADITIONAL CENTER Sec. 60-550







Key Features

- Vibrant and active interaction between public and private realms Larger buildings Front facade detailing Bay windows ٠ ٠
- .
- .
- Balconies .
- Street trees ٠
- More urban density •



Sec. 60-550.1 BUILDING PLACEMENT & CONFIGURATION T-5.1



PRINCIPAL BUILDING PLACEMENT:			
Front Setback, Principal:	0 ft Min, 10 ft Max (A)		
(Corner Lot) Front Setback, Secondary:	0 ft Min, 10 ft Max (B)		
Side Setback:	0*-5 ft Min (C)		
	*Subject to Building Permit Approval		
Rear Setback:	10 ft Min (D)		
Building Lot Coverage:	75% Max		
Useable Open Space:	5% Min		
Frontage Build-Out:	75% Min (along Front Setback, Primary)		
Lot Width:	24 ft Min, 160 ft Max		
PRINCIPAL BUILDING CONFIGURATION:			
Building Width:	14 ft Min, 150 ft Max (E)		

Sec. 60-550.2

BUILDING FRONTAGES



BUILDING FRONTAGE TYPES:	Stoop, Storemont and Gallery
BUILDING ENTRIES:	Primary entry door is encouraged along ground story facade facing a primary street.
BUILDING ENVELOPE ARTICULATION:	

Ground Story Building Frontage Facade:	Windows and doors shall comprise a minimum of 25% and maximum 60% coverage of the total ground story facade frontage.
Upper Story Building Frontage Facade:	Windows and doors shall comprise a minimum of 20% and maximum 40% coverage of the total upper story facade frontage.
Ground Story Finished Floor Elevation:	<u>Residential-</u> The ground story elevation must be a minimum of 2 feet minimum to 6 feet maximum above the front yard elevation (average grade). <u>Commercial</u> - The ground story elevation must be at a minimum of sidewalk grade to maximum of 2 feet.
Front Facade Wall:	Blank lengths of wall exceeding 10 linear feet are prohibited.

EXTERNAL ELEMENTS

Front Yard Fence:	Residential- A front yard fence a minimum of 2 feet and a maximum of 4		Formatted: Font: +Body, Not Superscript/ Subscript
	feet in height is encouraged to maintain spatial edge of street. No chain link, vinyl, split rail, or barbed wire is allowed.		Formatted: Font: +Body, Not Superscript/ Subscript
			Formatted: Font: +Body
Street Wall/Wall Opening:	A vehicle entry way, as part of a street wall, shall be a maximum width of 20 feet (residential) and 24 feet (commercial); a pedestrian entry way shall be a maximum width of 6 feet.	-	
Building Projections:	No part of any building, except overhanging eaves, awnings, balconies, bay windows, stoops and other architectural features shall encroach beyond the minimum front setback line.	-	
Stoop Encroachments:	Stoops may encroach upon the front setback line by the following distances but not encroach in the street right of way.		
Garages:	Detached garages shall be located a minimum of 20 feet from any street right of way.		
Driveways:	Driveways are encouraged to be on the secondary street frontage. Driveways shall be paved and a minimum of 8 feet wide and a maximum of 20 feet wide.		Formatted: Font: +Body, Not Superscript/ Subscript Formatted: Font: +Body, Not Superscript/ Subscript
Parking:	Residential-Vehicle parking areas shall be located only on driveways or designated parking areas and shall not extend into the street right of way or sidewalk. <u>Commercial</u> - Parking shall be located to rear of the property to the greatest extent possible. Parking on a side yard is limited to no more than 60 feet wide or 40% of the lot width. Screening and/or street wall is required for parking areas along a street.	- (Formatted: Font: +Body, Not Superscript/ Subscript
Accessory Structures:	Accessory structures shall be located a minimum of 20 feet from any street right of way and 5 feet from either side or rear property line.		
Landscaping:	Landscaping is encouraged but shall not extend into any street sidewalk or travel way. Street trees are encouraged.		
Foundation Planting:	Foundation plantings are encouraged but should be pruned and maintained with enough clearance from the building facade to encourage air circulation.	-	