

City of Auburn, Maine Capital Investments & Purchasing [CIP] Dan Goyette, Director 60 Court Street | Auburn, Maine 04210 www.auburnmaine.gov | 207.333.6601

June 26, 2023

Dear Bidder;

The City of Auburn is accepting written Bids for the Auburn Public Works Department for **Two (2) 4X4 One Ton Dump Trucks with Plow Gear.** The City reserves the right to accept or reject any or all Bids in whole or in part and to waive any informality the City may determine necessary. The City also reserves to itself the exclusive right to accept or reject any Bids when it is deemed by the City to be in its best interest. The City of Auburn is governed by Title 1 M.R.S.A. § 401-410, otherwise known as the Freedom of Information Act, which considers bid specifications as public documents. In awarding any Bid, the City may consider, but not be limited to, any of the following factors: Bidder qualifications, price, experience, financial standing with the City, warranties, references, bonding, delivery date, and service of Bidder. Successful Vendors/Contractors shall be current on all amounts due to the City of Auburn prior to the City entering into any contract agreement. All bids must include FOB to Auburn, Maine unless otherwise specified.

Bids will not receive consideration unless submitted in accordance with the following instructions. Please mark sealed envelopes plainly: <u>"Two (2) 4X4 One Ton Dump Trucks with Plow Gear – BID #</u> <u>2024-003"</u>.

Please contact Scott Holland, Deputy Director, with questions regarding this RFP or to schedule an appointment to view trade ins at (207) 333-6601, ext. 2155 or <a href="mailto:sholland@auburnmaine.gov">sholland@auburnmaine.gov</a>.

Please submit your Bid to the City of Auburn by 2:00 p.m. on Thursday, July 13, 2023. **Bids must be delivered to Derek Boulanger, Facilities Manager/ Purchasing Agent, 60 Court Street, Auburn, Maine 04210** on or before the date and time appointed. No Bids will be accepted after the time and date listed above.

Sincerely,

Derek<sup>L</sup>Boulanger Facilities Manager/Purchasing Agent

## **CONDITIONS AND INSTRUCTIONS TO BIDDERS**

- 1. Bidders shall use the enclosed bid form for quotations. Whenever, in bid forms, an article is defined by using a trade name or catalog number, the term "or approved equal", if not inserted, shall be implied.
- 2. Submit a separate unit price for each item unless otherwise specified in the bid request. Award will be made on a basis of each item, or as a group, whichever is in the best interest of the City. Prices stated are to be "delivered to destination".
- Bid proposals must be completed in full, in ink and must be signed by firm official. Bid proposal <u>must be notarized</u> prior to bid being sealed and will be disqualified if not notarized. Bids may be withdrawn prior to the time set for the official opening.
- 4. Bids will be opened publicly. Bidders or representatives may be present at bid opening.
- 5. Awards will be made to a responsible bidder, considering the quality of the materials, date of delivery, cost which meets specification and is in the best interest to the City of Auburn.
- 6. All transportation charges, including expense for freight, transfer express, mail, etc. shall be prepaid and be at the expense of the vendor unless otherwise specified in the bid.
- 7. The terms and cash discounts shall be specified. Time, in connection with discount offered, will be computed from date of delivery at destination after final inspection and acceptance or from date of correct invoice, whichever is later.
- 8. The City is exempt from payment of Federal Excise Taxes on the articles not for resale, Federal Transportation Tax on all shipments and Maine Sales Tax and Use Taxes. Please quote less these taxes. Upon application, exemption certificate will be furnished with the Purchase Order when required.
- 9. Time of delivery shall be stated. If time is of the essence, the earliest date may be a factor in the bid award.
- 10. No contract may be assigned without the written consent of the Finance Director or her designate. The contract shall not be considered valid until a purchase order has been issued to the successful bidder.
- 11. Please state <u>**"Two (2) 4X4 One Ton Dump Trucks with Plow Gear BID #2024-003"</u> on submitted sealed envelope.</u>**
- 12. The City of Auburn reserves the right to waive any formality and technicality in bids whichever is deemed best for the interest of the City of Auburn.

### **GENERAL CONDITIONS**

### **1. Equal Employment Opportunity**

The City of Auburn is an Equal Opportunity Employer and shall not discriminate against an applicant for employment, and employee or a citizen because of race, color, sex, marital status, physical and/or mental handicap, religion, age, ancestry or natural origin, unless based upon a bona-fide occupation qualification. Vendors and contractor or their agents doing business with the City shall not violate the above clause or the Civil Rights Acts of 1964. Violations by vendors shall be reviewed on a case-by-case basis and may mean an automatic breach of contract or service to the City of Auburn.

#### 2. Save Harmless

The Bidder agrees to protect and save harmless the owner from all costs, expenses or damages that may arise out of alleged infringement of patents of materials used.

### 3. Subcontracting

The Bidder shall not subcontract any part of the work or materials or assign any monies due it without first obtaining the written consent of the municipality. The Bidder is responsible for all approved sub-contracted work. The Bidder is responsible for managing all aspects of sub-contracting work. Neither party shall assign or transfer its interest in the contract without the written consent of the other party.

#### 4. Warranty

The Bidder warrants that all work will be of good quality and free from faults and defects, and in conformance with the specifications. All work not so conforming to these standards may be considered defective. The Bidder agrees to be responsible for the acts and omissions of all of its employees and all subcontractors, their agents and employees, and all other persons performing any of the work under a contract with the Bidder. If these specifications, either in whole or in part, do not meet all Federal and State of Maine DOT and ICC mandates it shall be the responsibility of the successful bidder to bring specifications into compliance prior to awarding bid.

## PROPOSAL FORM:

Due Thursday, July 13, 2023

To: City of Auburn Derek Boulanger, Facilities Manager/Purchasing Agent 60 Court Street Auburn, ME 04210

The undersigned individual/firm/business guarantees this price for thirty days (30) from the proposal due date. The undersigned submits this proposal without collusion with any other person, individual, or firm or agency. The undersigned ensures the authority to act on behalf of the corporation, partnership or individual they represent; and has read and agreed to all of the terms, requests, or conditions written herein by the City of Auburn, Maine.

By signing this form, the firm listed below hereby affirms that its bid meets the minimum specifications and standards as listed above.

Signature	Company	
Name (print)	Telephone #	
Title	Fax #	
Address		
Email Address		
Web Site		
STATE OF MAINE		
, SS.	Date:	

Personally, appeared \_\_\_\_\_\_ and acknowledged the foregoing instrument to be his/her free act and deed in his/her capacity and the free act and deed of said company.

Notary Public

Print Name

Commission Expires \_\_\_\_\_

## SPECIFICATIONS FOR: 2 Current Model Year or 2024 4X4 One Ton Dump Trucks with Plow Gear

# Trade-ins: (trade-ins will be available and transacted on date of delivery of new equipment.) FAILURE TO ANSWER ALL QUESTIONS COULD LEAD TO REJECTION OF BID

	Yes	No	Var.
Gasoline Engine Minimum 430 HP/475 lbs torque			
10 speed Automatic			
Minimum of 380 Amp Heavy Duty (Optional 2 alternators if needed)			
Dual 750CCA 78AH			
Front axle spring minimum 7000 lbs. Rear axle dual rear wheel, leaf spring minimum 12,000 lbs. Limited slip differential with axle ratio of 4.88 Shock absorbers must be extra heavy-duty Gas			
Four Wheel Disc with Anti-Lock Brake system (ABS)			
Power steering with steering damper			
Minimum of 30-gallon tank mounted to provide a clean frame rail for dump body installation. Fuel tank neck must come to the edge of the truck body. Truck beds that must be lifted to be fueled are unacceptable.			
BUMPER - FRONT         Tow hook front (2) mounted in such a way as no not interfere with the operation of the plow and rated for a minimum of 12,000 lbs.			
Manually telescoping two-way tilt/ trailer tow with west coast type,			
power/heated glass. Rear view standard			
19.5" Steel wheels Duel rear wheels			
225/70R/x 19.5 G BSW traction One spare tire and wheel			
Power windows, Power Locks, fixed rear window			
Factory installed			
AM/FM/ stereo with clock and aux port			
Full length vinyl with all weather water collecting rubber floor mats			
All functions must be by the use of a gauge Tachometer gauge Speedometer gauge Voltmeter gauge Engine Temperature gauge Fuel gauge			
	10 speed Automatic         Minimum of 380 Amp Heavy Duty (Optional 2 alternators if needed)         Dual 750CCA 78AH         Front axle spring minimum 7000 lbs.         Rear axle dual rear wheel, leaf spring minimum 12,000 lbs.         Limited slip differential with axle ratio of 4.88         Shock absorbers must be extra heavy-duty Gas         Four Wheel Disc with Anti-Lock Brake system (ABS)         Power steering with steering damper         Minimum of 30-gallon tank mounted to provide a clean frame rail for dump body installation. Fuel tank neck must come to the edge of the truck body. Truck beds that must be lifted to be fueled are unacceptable.         Tow hook front (2) mounted in such a way as no not interfere with the operation of the plow and rated for a minimum of 12,000 lbs.         Manually telescoping two-way tilt/ trailer tow with west coast type, power/heated glass. Rear view standard         19.5" Steel wheels         Duel rear wheels         225/70R/x 19.5 G BSW traction         One spare tire and wheel         Power windows, Power Locks, fixed rear window         Factory installed         AM/FM/ stereo with clock and aux port         Full length vinyl with all weather water collecting rubber floor mats         All functions must be by the use of a gauge         Speedometer gauge         Voltmeter gauge	10 speed Automatic         Minimum of 380 Amp Heavy Duty (Optional 2 alternators if needed)         Dual 750CCA 78AH         Front axle spring minimum 7000 lbs.         Rear axle dual rear wheel, leaf spring minimum 12,000 lbs.         Limited slip differential with axle ratio of 4.88         Shock absorbers must be extra heavy-duty Gas         Four Wheel Disc with Anti-Lock Brake system (ABS)         Power steering with steering damper         Minimum of 30-gallon tank mounted to provide a clean frame rail for dump body installation. Fuel tank neck must come to the edge of the truck body. Truck beds that must be lifted to be fueled are unacceptable.         Tow hook front (2) mounted in such a way as no not interfere with the operation of the plow and rated for a minimum of 12,000 lbs.         Manually telescoping two-way tilt/ trailer tow with west coast type, power/heated glass. Rear view standard         19.5" Steel wheels         Duel rear wheels         225/70R/x 19.5 G BSW traction One spare tire and wheel         Power windows, Power Locks, fixed rear window         Factory installed         AM/FM/ stereo with clock and aux port         Full length vinyl with all weather water collecting rubber floor mats         All functions must be by the use of a gauge         Tachometer gauge         Speedometer gauge         Voltmeter gauge         Engine Temperature gauge <td>10 speed Automatic       Iminimum of 380 Amp Heavy Duty         Minimum of 380 Amp Heavy Duty       (Optional 2 alternators if needed)         Dual 750CCA 78AH       Iminimum 7000 lbs.         Rear axle dual rear wheel, leaf spring minimum 12,000 lbs.       Imited slip differential with axle ratio of 4.88         Shock absorbers must be extra heavy-duty Gas       Iminimum of 30-gallon tank mounted to provide a clean frame rail for dump body installation. Fuel tank neck must come to the edge of the truck body. Truck beds that must be lifted to be fueled are unacceptable.         Tow hook front (2) mounted in such a way as no not interfere with the operation of the plow and rated for a minimum of 12,000 lbs.         Manually telescoping two-way tilt/ trailer tow with west coast type, power/heated glass. Rear view standard         19.5" Steel wheels         Duel rear wheels         225/70R/x 19.5 G BSW traction         One spare tire and wheel         Power windows, Power Locks, fixed rear window         Factory installed         AM/FM/ stereo with clock and aux port         Full length vinyl with all weather water collecting rubber floor mats         All functions must be by the use of a gauge         Tachometer gauge         Speedometer gauge         Expendence         AM/FM/ stereo with clock and aux port         Full length vinyl with all weather water collecting rubber floor mats         All functio</td>	10 speed Automatic       Iminimum of 380 Amp Heavy Duty         Minimum of 380 Amp Heavy Duty       (Optional 2 alternators if needed)         Dual 750CCA 78AH       Iminimum 7000 lbs.         Rear axle dual rear wheel, leaf spring minimum 12,000 lbs.       Imited slip differential with axle ratio of 4.88         Shock absorbers must be extra heavy-duty Gas       Iminimum of 30-gallon tank mounted to provide a clean frame rail for dump body installation. Fuel tank neck must come to the edge of the truck body. Truck beds that must be lifted to be fueled are unacceptable.         Tow hook front (2) mounted in such a way as no not interfere with the operation of the plow and rated for a minimum of 12,000 lbs.         Manually telescoping two-way tilt/ trailer tow with west coast type, power/heated glass. Rear view standard         19.5" Steel wheels         Duel rear wheels         225/70R/x 19.5 G BSW traction         One spare tire and wheel         Power windows, Power Locks, fixed rear window         Factory installed         AM/FM/ stereo with clock and aux port         Full length vinyl with all weather water collecting rubber floor mats         All functions must be by the use of a gauge         Tachometer gauge         Speedometer gauge         Expendence         AM/FM/ stereo with clock and aux port         Full length vinyl with all weather water collecting rubber floor mats         All functio

		Yes	No	Var.
SEAT	Heavy Duty Vinyl, 40/20/40 split bench with center armrest			
AIRBAGS	Standard			
STEPS	Running boards or steps			
TOW PACKAGE	Trailer Brake controller and wiring kit installed and operational			
BODY STYLE & WHEELBASE	Regular cab dual wheel chassis, 145" wheelbase, 60" CA. Must accommodate 9' dump body GVW of 16,500 minimum Payload of up to 8,000 lbs. Clean frame rail from back of cab to end of frame Cab color White			
DUMP BODY	<ul> <li>9 ft stainless steel body with drop hinge sides</li> <li>Body height Maximum of 42' from top of frame</li> <li>12" side height with brackets for sideboards</li> <li>Front panel with 12"x18" expanded steel center of panel for use of rear-view mirror</li> <li>18" two-way tailgate</li> <li>Rubber mud flaps with anti-sail attached to the dump body before and after wheels both left and right sides.</li> <li>Continuously welded construction</li> <li>Capacity of 2-3 cu yds.</li> <li>Total height cannot be more than 84" from ground, incl. Lights</li> <li>Body up light to be mounted in dash</li> </ul>			
HYDRAULIC HOIST SYSTEM	Direct lift with sub frame four (4) ton lift hoist Double acting cylinders Electric over hydraulic Body safety prop			
TRAILER HITCH PLATE	Pintle plate installed between frame rails ½" steel minimum. Pintle hitch installed with 8 drilled holes to adjust height of 8-ton rated hitch Trailer plug in connector must be 7 pin round and installed in pintle plate All Wiring connections shall be soldered, sealed in shrink-wrap, covered with high temperature corrugated loom and protected			
PAINT	Truck body White standard with proper prep and primer Body Stainless Steel All bolt on parts are painted prior to assembly. All wiring, parts, are not to be painted. All parts added/fabricated are sandblasted prior to painting. Auto primer on all parts 2 (two) coats primer and two coats finish Pintle plate painted to match frame			

		Yes	No	Var.
	Front: LED amber/green strobe lights mounted in front corners of the headboard, 4 total, 2 facing forward and 1 on each side as to be seen from both front and sides of vehicle. All switches to be dash mounted and labeled.			
	Rear: Stop/Tail/turn to be standard light (not LED). Mounted outside frame rails. Amber LED strobes are to be mounted in boxes or corner posts in the rear on the left and right of the body			
EMERGENCY LIGHTING/SAFETY	Amber LED arrow stick mounted on the top of the headboard below the lip (not show above the top of headboard) facing rear. A separate control switch shall be mounted in the cab, arrow stick left, right and flashing operation signals.			
	Back up alarm mounted in rear on/near pintle plate area			
	5 lb. ABC Fire extinguisher mounted in cab in quick release mount			
SNOWPLOW	Fisher 9'-6" Stainless Steel Extreme V with intensifire LED lights			
EQUIPMENT	Double acting cylinders			
	Top rubber snow deflector Fisher Poly-Cast Hopper Spreader 8' 1.8 cu yd, Inverted V/Vibrator			
SANDER	or equivalent			
MANUALS	One parts, operation, and service manuals. Diagnostic Multi-function port with software and hardware to read included. Any updates that come later must be free to the city, when made available to the vender.			
WARRANTY & DELIVERY	Three (3) year front to back warranty on all components Unit to be fully functioning upon delivery. Or a \$100.00 dollar per calendar day penalty is incurred, for everyday it is not complete. Optional Five (5) year warranty front to back All safety, operation, and instruction are required upon delivery of the unit by a factory-trained technician. Free annual training as requested from the City of Auburn. If during the first three years any warranty or work is needed including parts that require the unit to be out of service for more than 48 hours. A comparable loaner unit will be provided to the City at no cost. Any parts that cannot be shipped FOB to the City of Auburn within 48 hrs. will be discounted at 15 % per calendar day. All Wiring connections shall be soldered, sealed in shrink-wrap, covered with high temperature corrugated loom and protected			

## **Exceptions and Deviations:**

Bidder shall fully describe every variance, exception, and/or deviation. If additional space is needed, please include additional sheets.

### **PRICE PROPOSAL FORM**

The undersigned proposes to furnish Two (2) Current MODEL YEAR or 2024 4X4 One Ton Dump Truck with Plow Gear other accessories in accordance with the Instruction to Bidders and Specifications, both of which are incorporated herein by reference. All components will be complete without the need to modify, fabricate or re-route hoses, wiring, hydraulic to make it fit.

# Two (2) Current MODEL YEAR or 2024, Four Wheel Drive 16,500 lb. GVW-One Ton Dump Trucks with Plow Gear

	\$
Make and Model and Year	
Associated Equipment	
Less Trades: (2) 2009 F450's w/plow and sander	
(Where is, as is, no implied guarantee at time of trade	-in.) \$
Net FOB Auburn Highway Garage (Total Price)	\$
Please provide additional pricing for the following	options:
Diesel Engine Minimum of 300HP	\$
Delivery Date:	
Name of Company:	
Signed by:	
Print Name:	
Title:	
Address:	
Email:	